Aquarius Distibution > Aquaseal > FlashRite



FlashRite

- · Suitable for both standard and retrofit application
- Wraps around existing pipes
- · Suitable for repairs
- Full range of sizes
- Polymer is Ozone and UV resistant
- 25 year warranty
- BAL tested*
- Australian Made & Owned

Retro Fit Clips are sold separately



Size Chart

Aquaseal FlashRite	Black EPDM Code	Red Silicone Code	Grey EPDM Code	METRIC: Pipe Size (25° roof pitch)	METRIC: Pipe Size (45° roof pitch)	IMPERIAL: Pipe Size (25° roof pitch)	IMPERIAL: Pipe Size (45° roof pitch)	Base Size	Max retrofit clips required
Mini	AFE0B3-20	AFS0R3-20	AFE0G3-20	3-25mm	3-20mm	1/2"-1"	1/3"-34"	80x80mm	n/a
No. 1	AFE1B5-45	AFS1R5-45	AFE1G5-45	5-50mm	5-40mm	½"-2"	1/5"-11/2"	120x120mm	n/a
No. 2	AFE2B25-70	AFS2R25-70	AFE2G25-70	25-70mm	25-65mm	1"-2¾"	1"-2½"	163x163mm	3
No. 3	AFE3B50-100	AFS3R50-100	AFE3G50-100	50- 100mm	50-80mm	2"-4"	2"-31/8"	210x210mm	4
No. 4	AFE4B90-150	AFS4R90-150	AFE4G90-150	90- 150mm	90- 130mm	3½″-6″	3½"-5"	260x260mm	5
No. 5	AFE5B125-200	AFS5R125-200	AFE5G125-200	125- 200mm	125- 165mm	5"-8"	5"-6½"	313x313mm	5
No. 6	AFE6B150-230	AFS6R150-230	AFE6G150-230	150- 250mm	150- 230mm	6"-10"	6"-9"	370x370mm	6
No. 7	AFE7B200-300	AFS7R200-300	AFE7G200-300	195- 300mm	195- 255mm	8"-11%"	8"-10"	440x440mm	7

^{*}EPDM will withstand constant temperatures of -40°C (-40°F) to 115°C (239°F).

Australian Owned & Made

^{*}Silicone will withstand constant temperatures of -50°C (-58°F) to 200°C (392°F).

^{*}EPDM black certified for installation to BAL 12.5 rated roof/wall systems

^{*}Silicone red certified for installation to BAL 29 rated roof/wall systems

Installation Overview STEPS 2 & 3 ONLY IF RETRO-FITTING OCIT CONE TO EXACT CORRESPONDING PIPE DIAMETER. OCIT CONE TO EXACT CORRESPONDING PIPE DIAMETER.

8 REALIGN FLASHING ONTO ROOF AND FIX WITH APPROPRIATE FASTENERS. START HERE.

APPLY SEALANT ON MARKED PATH