2001941	K2 Single Rail 36, 4.15 m	Quick mounting rail with static confirmation. With side connection. Mounting with K2 Climber 36/48 or with K2 SingkeHook. The rail span width amounts to 1350mm at K2 standard conditions. Material: Aluminium EN AW-6063 T66
2001865	K2 Single Rail 36, <mark>2.10 m</mark>	Quick mounting rail with static confirmation. With side connection. Mounting with K2 Climber 36/48 or with K2 SingkeHook. The rail span width amounts to 1350mm at K2 standard conditions. Material: Aluminium EN AW-6063 T66
2001976	Rail connector K2 Single Rail 36 Set	Aluminium rail connector as connecting element between two K2 SingleRail 36. Set consists of: 1xSingkeRail connector 36 (2001975), aluminium EN AW-6063 T66. 4xT-Bolts M8x20 Stainless Steel. 4xlocking nut M8, Stainless Steel
2002341	SOLAR MOUNTING PROFILE MODULE MOUNTING RAIL MINIRAIL SET - Length 0,38 m - The MiniRail System allows portrait and landscape mounting in the form of grid mounting thanks to the universal module clamps, which are rotatable by 90°. Self-tapping screws Included in MiniRail MC/EC set with sealing washers - Pitched roofs with trapezoidal sheet metal or sandwich panels Roof inclination: 5 - 75°	Short rail for mounting solar modules on trapezoidal sheet metal roofs, incl. 4 threadforming tapping screw with sealing washer. The set consists of: 1 x MiniRail with EPDM, aluminium EN AW-6063 T66/ EPDM 4 x thread-forming tapping screw with EPDM (1005207), stainless steel A2